

SINCE 1978



LEADING LIGHT

Product Datasheet

vkleadinglight.gr

Loop

VK/04717/GL/DA/GDB/W/60


Satin Gold+black. 3000K. 367lm. 7W. CRI>90. 60cm Led track light. Input voltage DC48V. Dimmable Dali. Diffuse Light. Led Bridgelux E6 CA-A. 50.000 hrs. -20°C → 45°C. Aluminum. IP20





IP20



Dimensions



Gallery






Downloads




VK Leading Light

Since 1978

Technical Specifications	
Kelvin	3000K
Power	7W
Voltage	48V
Extra	
Fitting	Led track light
Type	Light
Safety class	
Light source	Bridgelux
IP Rating	IP20
CRI	CRI>90
Dimmable	
Lifetime	50.000hrs
Working temperature	-20°C-45°C
PAGE	42 New Products 2026
NICKNAME	Loop

Physical Specifications	
Family	Loop
Color	Satin Gold+black
Material	Aluminum
Width	ø2cm (track line) (ø9cm globe)
Length	60cm (track line) (ø9cm globe)
Height	ø2cm (track line)
Width (inner box)	140cm
Length (inner box)	165cm
Height (inner box)	640cm

Illumination Data

Lumen	367lm
Beam angle	Diffuse light
Lighting direction	

Packing Info

Pcs/carton	12pcs
------------	-------

Certification & Warranty

Guarantee	3 years
-----------	---------

Energy Label



VK LEADING LIGHT
VK/04717/GL/DA/GDB/W/60

A	▶
B	▶
C	▶
D	▶
E	▶
F	◀
G	▶

5 kWh/1000h



2019/2015