Baby Marge




Table Lamps | 220-240 V | 1 x powerLEDs 0.5 W DC RGB **15000**



Technical data		
Туре	Table Lamps	
Installation position	Floor	
Installation environment	Indoor	
Light Source	LED	
Optics	General Lighting	
Light emission direction	upward	
Power	0.5 W	
Frequency	60 - 50 Hz	
CCT / Tone	RGB	
C.C. / C.V.	AC	
Safety class	2	
IP	IP65	
IK	IK06	
Glow wire test	650°	
Direct mounting on normally flammable surfaces	Yes	
CE	Yes	
Driver included	Driver	
Dimmable article	No	
Min duration	12 h	
Max duration	14.5 h	
Charging time	6 h	
Directional	No	
Tilting	No	
Walk-over	No	
Drive-over	No	
Cable included	Yes	
Cable length	2 m	
Electric socket	Type C	
Resin potting	No	
ype of light emission Double em		
Net weight	0.846 Kg	
Electrostatic discharge protection	No	
Surge protection	No	





Finishing diffuser		
Material	PE	
Colour	neutral	
Finishing mou	unting frame	
Material	PE	

white

Colour

Baby Marge



Table Lamps | 220-240 V | 1 x powerLEDs 0.5 W DC $\,$ | RGB 15000

Double emission table lamps for indoor application. The RGB LED light source with a general lighting light distribution is composed of 1 powerleds LEDs.

The diffuser is made of pe; the mounting frame is made of pe, with a white finish. The ingress protection degree is IP65; the total weight is of 0.846 kg.

The total absorbed power is W. The power supply cable is included and features a 2 m lenght.

The device features protection class II and can be floor-mounted.

Compliant with the EN 60598-1 standard and its specific provisions.

LED Life / Failure Ratio

L80 B20 C0 80000h