



29442089



ε



## Universal rotary dimmer with centre plate (R, L, C, LED) with soft-lock, Serie R.classic, polar white glossy

Technical features

### Functions

- bulb-preserving soft startup

### Controls and indicators

- with soft-lock

### Main electrical features

Nominal voltage 230 V

Frequency 50/60 Hz

### Voltage

Operating voltage 230 V AC

- voltage test possible without dismantling

### Fuse

Fuse short-circuit and overload proof (electronic fuse)

### Power

Dimmable conventional transformers 20...420 VA

Loss power at full load ≈ 4 W

Electronic transformers 20...420 W

### Measurement

Extension unit input with input for extension units insert for universal rotary dimmer, with extension unit input for push-button (NO contact) with single-surface operation

### Materials

Colour of design line polar white

Colour polarwhite

Material Plastic/metal

### Dimensions

Insertion depth 24 mm

Axis dimension Ø 4 mm

### LED control

Dimmable 230 V retrofit LED lamps 3...100 W

### Incandescent bulbs control

230 V incandescent lamps and halogen lamps 20...420 W

### Installation, mounting

Installation mode with spreader claws

---

**Connection**

---

Type of load	Universal and LED Retrofit
Conductor cross-section	0,5...4 mm <sup>2</sup>
- with screw terminals	

---

**Scope of delivery**

- with incremental encoder
- 

**Equipment**

- phase cut-on, cut-off or LED phase cut-on according to load type, self-learning
  - with brightness memory
- 

**Use**

---

Differentiation characteristic 3 - Sales	with soft-lock
--	----------------

---

**Identification**

---

Application, usage	Light control
Main design line	Serie R.classic

---