

KALIO SQUARE

308-30039600

KALIO SQUARE R RECESSED SPOTLIGHT made of aluminium, black, similar to RAL 9005, beam 38°, light output direct, tilting 45°, without converter, max. 250mA, dimmability: see converter, IP20




DRAWING




45°

1 - 20 mm

 Ø 80 mm, **ET 83 mm**


LIGHT DISTRIBUTION CURVE



TECHNICAL DETAILS

System perform. [W]	9
Bulb type	LED 9W
Luminous flux [lm]	900
Current sec. [mA]	250
Colour temp. [K]	3000K
CRI	>90
Converter	without converter
Dimming	see converter
Light output	direct
Beam angle [°]	38°
Voltage [V]	36 VDC
Material	aluminium
Length [mm]	96
Width [mm]	96
Height [mm]	53
Ceiling cutout [mm]	80
Ceiling thickness [mm]	1-20
Recess depth [mm]	83
IP protection class	IP20
Voltage class	protection cl. III
Net weight [kg]	0,16
Colour lamp	black
RAL	9005
EAN-Number	9010506140026
Lifetime [h]	L80 B10 S0 000
Energy efficiency cl.	E



The values are rated values. Power and luminous flux are initially subject to a tolerance of +/- 10%. Colour temperature tolerance: +/- 150 K. The values apply to an ambient temperature of 25°C unless otherwise specified.