



<b>Housing Material</b>	Aluminium
<b>Housing Color</b>	White
<b>Material of Lens</b>	PMMA
<b>Functions</b>	Dim to warm
<b>Protection Class</b>	Protection class I/protective grounding
<b>Rated Input</b>	10 W
<b>Rated Power Consumption Standby</b>	0.5 W
<b>Rated Input Voltage Frequency</b>	200-240 V/AC 50 / 60 Hz
<b>Power Supply Unit incl.</b>	Yes
<b>Dimmable</b>	Yes
<b>Control technology</b>	Leading-edge dimmer, Trailing-edge dimmer
<b>Motion Detector</b>	No
<b>Light Source</b>	LED, Light source changeable TC
<b>Colour Temperature</b>	1800-2700 K
<b>Colour Rendering Index (Ra)</b>	90
<b>Rated Luminous Flux</b>	750 lm
<b>Rated Angle of Reflection</b>	36 Degree
<b>Light Distribution</b>	Symmetric
<b>Height</b>	218 mm
<b>Diameter</b>	65 mm
<b>Working Temperature</b>	-20 to 40 °C
<b>Storage Temperature</b>	-20 to 65 °C
<b>IP Protection Class</b>	IP 20
<b>Life Time L70 / B50</b>	50000 h
<b>Switching Cycles</b>	100000
<b>Energy Efficiency Class Lightsource</b>	This product contains a light source of energy efficiency class F.