



The CAN angular surface-mounted ceiling light offers a flexible lighting solution for commercial and private spaces. Available as a one, two and three-lamp version in black and white, it enables precise alignment of the light thanks to the rotatable and swivelling light body. The widely used GU10 base makes it easy to replace the light source quickly and the screw-on cylinder housing enables tool-free access. Thanks to the integrated plug-in terminals, installation for rigid and flexible cables is simple and efficient. The CAN surface-mounted ceiling light is part of a versatile series that also includes pendant, wall, reading and outdoor lights.

#### Special features

- flat and discreet luminaire base
- can be customised with cylinder housing in 6 different colours

<b>Housing Material</b>	Aluminium
<b>Housing Color</b>	White
<b>Protection Class</b>	Protection class I/protective grounding
<b>max. Power</b>	1x max. 7.5 W
<b>Rated Input Voltage Frequency</b>	220-240 V/AC 50 / 60 Hz
<b>Socket Description</b>	GU10
<b>Socket Quantity</b>	1 PCS
<b>Dimmable</b>	Yes
<b>Control</b>	Dimmable via optional light source
<b>Motion Detector</b>	No
<b>Execution</b>	Without lamp
<b>Swivel Angle</b>	90 Degree
<b>Rotation Angle</b>	350 Degree
<b>Light Exit Surfaces</b>	1
<b>Light characteristics</b>	Direct
<b>Light direction</b>	Below
<b>Length</b>	110 mm
<b>Width</b>	90 mm
<b>Height</b>	58 mm
<b>Base length</b>	110 mm
<b>Base width</b>	90 mm
<b>Base height</b>	15 mm
<b>Product weight</b>	175 g
<b>Working Temperature</b>	-5 to 40 °C
<b>Storage Temperature</b>	-20 to 60 °C
<b>IP Protection Class</b>	IP 20