


MUSO

501-r2819150


MUSO ROUND SD SURFACE MOUNTED CEILING LUMINAIRE made of synthetic, white, similar to RAL 9003, polycarbonate cover beam 115°, light output direct, with converter, max. 250mA, dimmability: not dimmable, IP54



DRAWING



LIGHT DISTRIBUTION CURVE



TECHNICAL DETAILS

System perform. [W]	18
Bulb type	LED
Luminous flux [lm]	1750
Current sec. [mA]	250
Colour temp. [K]	3000K
CRI	>80
Optics	polycarbonate cover
Converter	with converter
Dimming	not dimmable
Light output	direct
Beam angle [°]	115°
Voltage [V]	220-240V 50/60Hz
Material	synthetic
Height [mm]	48
Diameter [mm]	280
IP protection class	IP54
Voltage class	protection cl. II
Shock resistance	IK08
Net weight [kg]	0,79
Colour lamp	white
RAL	9003
EAN-Number	9008905920806
Lifetime [h]	L80 B10 50 000
Energy efficiency cl.	E
No. of luminaires B16A	50



The values are rated values. Power and luminous flux are initially subject to a tolerance of +/- 10%. Colour temperature tolerance: +/- 150 K. The values apply to an ambient temperature of 25°C unless otherwise specified.