

**Special features**

- Customised lighting solution thanks to replaceable light source
- can be customised with cylinder housing in 5 different colours
- can be combined with the extensive product family of the CAN series

<b>Housing Material</b>	Aluminium
<b>Housing Color</b>	White
<b>Protection Class</b>	Protection class I/protective grounding
<b>max. Power</b>	1x max. 7.5 W
<b>Rated Input Voltage</b>	220-240 V/AC 50 / 60 Hz
<b>Frequency</b>	
<b>Socket Description</b>	GU10
<b>Socket Quantity</b>	1 PCS
<b>Diameter of Illuminant to be used max.</b>	50 mm
<b>Dimmable</b>	Yes
<b>Control</b>	Dimmable via optional light source
<b>Motion Detector</b>	No
<b>Execution</b>	Without lamp
<b>Swivel Angle</b>	90 Degree
<b>Rotation Angle</b>	350 Degree
<b>Light Exit Surfaces</b>	1
<b>Light characteristics</b>	Direct
<b>Light direction</b>	Below
<b>Height</b>	98 mm
<b>Diameter</b>	60 mm
<b>Installation Depth</b>	40 mm
<b>Cut Out Diameter</b>	51 mm
<b>Product weight</b>	277 g
<b>Working Temperature</b>	-5 to 40 °C
<b>Storage Temperature</b>	-20 to 60 °C
<b>IP Protection Class</b>	IP 20