

Art. no. 950218

Pendant lamp Lautaro 900/60 Down Opal M3, 59 W,
DALI, 2700 K, white



Special features

- DALI dimmable with integrated power supply
- continuous wiring possible
- tool-free connection with plug-in terminals
- easy to install / maintain
- long-lasting, easily replaceable components
- invisible screw connections
- customised designs available on request

Housing Material	Aluminium, Steel	IP Protection Class Lamp	IP 20
Housing Color	White	IK Protection Class	IK05
Material of Lens	Polycarbonate - PC		
Surface Structure of Lens	Opal		
		Life Time L70 / B50	180000 h
Protection Class	Protection class I/protective grounding	Life Time L80 / B10	120000 h
Rated Input	59 W	Life Time L80 / B50	130000 h
Rated Power Consumption Standby	0.3 W	Life Time L90 / B10	50000 h
Rated Input Voltage Frequency	198-264 V/AC 50 / 60 Hz	Life Time L90 / B20	60000 h
Power Supply Unit incl.	Yes	Switching Cycles	100000 PCS
Dimmable	Yes	Power Consumption	59 kWh/1000h
Control	DALI 2 / DT6, Push-Dim	Energy Efficiency Class Lightsources	This product contains a light source of energy efficiency class E.
Motion Detector	No		
Light Source	LED, Light source changeable TC		
Color Temperature	2700 K		
Colour Consistency	3 SDCM		
Colour consistency light source	2 SDCM		
CRI (Ra)	90		
Rated Luminous Flux	7080 lm		
Rated Angle of Reflection	90 Degree		
UGR	22		
Light Exit Surfaces	1 PCS		
Light characteristics	Direct		
Light direction	Below		
Height	60 mm		
Diameter	900 mm		
Pendulum Length max.	3000 mm		
Working Temperature	-20 to 50 °C		
Storage Temperature	-40 to 80 °C		
IP Protection Class	IP 20		