


Art. no. 950253

Pendant lamp Lautaro 900/60 Up/Down Opal M3, 84 W,
DALI, 2700 K, black

 **DEKO LIGHT**



Special features

- DALI dimmable with integrated power supply
- continuous wiring possible
- tool-free connection with plug-in terminals
- easy to install / maintain
- long-lasting, easily replaceable components
- invisible screw connections
- customised designs available on request

Housing Material	Aluminium, Steel
Housing Color	Black
Material of Lens	Polycarbonate - PC
Surface Structure of Lens	Opal
Protection Class	Protection class I/protective grounding
Rated Input	84 W
Rated Power Consumption Standby	0.3 W
Rated Input Voltage Frequency	198-264 V/AC 50 / 60 Hz
Power Supply Unit incl.	Yes
Dimmable	Yes
Control	DALI 2 / DT6, Push-Dim
Motion Detector	No

IP Protection Class Lamp	IP 20
IK Protection Class	IK05
Life Time L70 / B50	180000 h
Life Time L80 / B10	120000 h
Life Time L80 / B50	130000 h
Life Time L90 / B10	50000 h
Life Time L90 / B20	60000 h
Switching Cycles	100000 PCS
Power Consumption	59 kWh/1000h
Energy Efficiency Class Lightsource	This product contains a light source of energy efficiency class E.

Light Source	LED, Light source changeable TC
Color Temperature	2700 K
Colour Consistency	3 SDCM
Colour consistency light source	2 SDCM
CRI (Ra)	90
Rated Luminous Flux	10000 lm
Rated Angle of Reflection	90 Degree
UGR	22

Light Exit Surfaces	2 PCS
Light characteristics	Direct, Indirect
Light direction	Top, Below

Height	60 mm
Diameter	900 mm
Pendulum Length max.	3000 mm

Working Temperature	-20 to 50 °C
Storage Temperature	-40 to 80 °C
IP Protection Class	IP 20