



PROJECT _____

TYPE _____


NOTES _____

QUANTITY _____

DATE _____



Squared ceiling recessed downlight made from die-cast aluminium; with trim; surface White Matt powder coated; matt texture; with reflector made from plastic in Glossy White; installation without tools using wire springs; suitable for ceiling thickness of 4-28 mm; recessed depth 60 mm; PCB; light colour selectable via dip switch (2700K / 3000K); to be set before installation; beam angle 39°; degree of protection IP20; Class 3; driver not included; light source replaceable by Wever & Ducré or by a professional with explicit authorization;



LUMINAIRE

Ceiling _____
 Recessed _____
 Reflector: White _____
 RAL 9010 + No matching RAL _____
 a _____
 IP20 _____
 Interior _____
 125 lm _____

LED Module

2700 K / 3000 K _____
 CRI ≥ 90 _____
 L80 / 50000h _____
 ≤ 3 SDCM (initial MacAdam) _____

Optical

Medium (standard) _____
 beam angle 39° _____

Electrical

excl. driver _____
 6 V _____
 Class III _____
 Standard _____

Physical

diameter 43 mm _____
 height 40 mm _____
 0.05 kg _____
 wire springs _____

Cutout

length 36 mm _____
 width 39 mm _____
 min. ceiling thickness 4 mm _____
 max. ceiling thickness 28 mm _____
 recessed depth 60 mm _____

datasheet.quicksum.material

Aluminium _____

^a Colour may deviate slightly due to production conditions



ELECTRICAL ACCESSORIES

Driver

Type	Colour	Voltage	L·W·H (MM)	Item number
3.5W 350mA 2.7-10V		2,7-10V	65-29-18	90213102
7W 350mA 12-21V phase-cut dim		12-21V	68-33-22	90223301
14W 350mA 10-40V DALI-2 push dim		10-40V	166-29-21	90243502