



PROJECT

TYPE


NOTES

QUANTITY

DATE



Rectangular ceiling recessed downlight made from die-cast aluminium; with trim; with 2 spotlights; surface Black Matt powder coated; matt texture; with reflector made from plastic in Glossy Black; installation without tools using wire springs; suitable for ceiling thickness of 4-28 mm; recessed depth 60 mm; PCB; light colour selectable via dip switch (2700K / 3000K); to be set before installation; beam angle 39°; degree of protection IP20; Class 3; driver not included; light source replaceable by Wever & Ducré or by a professional with explicit authorization;



LUMINAIRE

Ceiling
 Recessed
 Reflector: Black
 RAL 9011 + No matching RAL ^a
 IP20
 Interior
 250 lm

LED Module

2700 K / 3000 K
 CRI ≥ 90
 L80 / 50000h
 ≤ 3 SDCM (initial MacAdam)

Optical

Medium (standard)
 beam angle 39°

Electrical

excl. driver
 12 V
 Class III
 Standard

Physical

length 70 mm
 width 43 mm
 height 40 mm
 0.07 kg
 wire springs

Cutout

length 36 mm
 width 67 mm
 min. ceiling thickness 4 mm
 max. ceiling thickness 28 mm
 recessed depth 60 mm

datasheet.quicksum.material

Aluminium

^a Colour may deviate slightly due to production conditions

109561BB9



ELECTRICAL ACCESSORIES

Driver

Type	Colour	Voltage	L·W·H (MM)	Item number
6W 350mA 8.6-18V		8.6-18V	67-39-22	90213303
7W 350mA 12-21V phase-cut dim		12-21V	68-33-22	90223301
14W 350mA 10-40V DALI-2 push dim		10-40V	166-29-21	90243502