



**PROJECT**

**TYPE**

**NOTES**

**QUANTITY**


**DATE**



IP44



Round shape ceiling surface luminaire made from die-cast aluminium; surface Black Matt; powder coated; matt texture; RAL 9011; opal PMMA cover; PCB 3-step binning; phase-cut dim; light colour 3000 K; binning initial MacAdam  $\leq 3$  SDCM; CRI  $\geq 90$ ; degree of protection IP44; Class 1; light source replaceable by Wever & Ducré or by a professional with explicit authorization;



**Luminaire**

Ceiling  
Surface  
Black Matt  
RAL 9011<sup>a</sup>  
IP44  
Interior  
1600 lm

**Module**

3000 K  
CRI  $\geq 90$   
L80 / 60000h  
initial MacAdam  $\leq 3$  SDCM  
2154 lm  
117 lm/W<sup>b</sup>

**Optical**

Opal  
CIE flux code: 46 77 95 99 100


**Electrical**

phase-cut dim  
220 - 240 V  
system 18.4 W  
Class 1

**Physical**

diameter 260 mm  
height 57 mm  
1.55 kg

**LIGHT DISTRIBUTION**



<sup>a</sup> Colour may deviate slightly due to production conditions

<sup>b</sup> Without electrical losses

**ELECTRICAL ACCESSORIES**

<b>Dimmer Type</b>	<b>Colour</b>	<b>Voltage</b>	<b>L·W·H (MM)</b>	<b>Item number</b>
for switch		230V	46·17.5·46	90019017
DIN RAIL	White	230V	17·55·90	90019018