



PROJECT

TYPE

NOTES

QUANTITY

DATE



Round shape ceiling surface luminaire made from die-cast aluminium; microprismatic PMMA cover; $UGR \leq 19$; VDU compatible workplace luminaire according to DIN EN 12464-1; luminance above $65^\circ \leq 3000 \text{ cd/m}^2$; surface Black Matt wet painted; matt texture; RAL 9011; with COB (Chip on Board) technology for maximum efficiency; DALI dim; light colour 4000 K; binning initial MacAdam $\leq 3 \text{ SDCM}$; $CRI \geq 90$; degree of protection IP20; Class 1; driver included; light source replaceable by Wever & Ducré or by a professional with explicit authorization; control gear replaceable by end-user;

Luminaire

Ceiling
Surface
Black Matt
RAL 9011 ^a
IP20
Interior
3660 lm

Module

4000 K
 $CRI \geq 90$
L80 / 80000 h
initial MacAdam $\leq 3 \text{ SDCM}$
3663 lm
106 lm/W ^b

Optical

Microprismatic
 $UGR \leq 19$
 $\geq 65^\circ < 3000 \text{ cd/m}^2$
CIE flux code: 65 89 97 100
100



Electrical

DALI-2
220 - 240 V
system 35 W
Class 1

Physical

diameter 560 mm
height 195 mm
4.2 kg

LIGHT DISTRIBUTION



^a datasheet.footnote.ral_footnote

^b datasheet.footnote.no-electrical-losses