



PROJECT

TYPE

NOTES

QUANTITY

DATE



Linear surface mounted ceiling luminaire with 2 multi-spot modules made from aluminium; housing Black Matt powder coated; matt texture; with reflector in Black Matt wet painted; matt fine texture; Polycarbonate lens and reflector; with COB (Chip on Board) technology for maximum efficiency; phase-cut dim; light colour 3000 K; CRI ≥ 90; degree of protection IP20; Class 1; driver included; optional honeycomb louver available, to reduce glare;

LUMINAIRE

Ceiling _____
 Surface _____
 rotation 90 ° _____
 Black Matt _____
 IP20 _____
 Interior _____
 1520 lm _____

LED Module

3000 K _____
 CRI ≥ 90 _____
 L70 / 55000h _____
 ≤ 2 SDCM (initial MacAdam) _____

Optical


Medium _____
 beam angle 32° _____

Electrical

phase-cut dim _____
 220 - 240 V _____
 system 22.0 W _____
 Class I _____
 Standard _____

Physical

Base _____
 length 754 mm _____
 width 51 mm _____
 height 92 mm _____
 1.15 kg _____
 On base _____



[173564BBB5] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.

173564BBB5



OPTICAL ACCESSORIES

Honeycomb Louver

Type	Colour	Voltage	Ø (MM)	Item number
BLIEK petit CENO LECA PIRRO QITO	Black		29	915230B0