





PROJECT

TYPE


NOTES

QUANTITY

DATE



Bedside luminaire made from die-cast aluminium with rectangular base; inclusive on/off switch in black; surface Black Matt; powder coated; matt texture; RAL 9011; with COB (Chip on Board) technology for maximum efficiency; light colour 2700 K; binning initial MacAdam ≤ 2 SDCM; CRI ≥ 90 ; beam angle 30°; 220 - 240 V; 350° rotatable and 90° tiltable; degree of protection IP20; Class 1; driver included; light source replaceable by Wever & Ducré or by a professional with explicit authorization; control gear replaceable by an authorized professional;



GENERAL

Wall
Surface
tilt max 90 °
rotation 350 °
Black Matt
RAL 9011^a
IP20
Interior
330 lm
CIE flux code: 97 100 100 100 100


LED

2700 K
CRI ≥ 90
L80 / 50000h
initial MacAdam ≤ 2 SDCM

OPTICAL

Standard
beam angle 30°

LIGHT DISTRIBUTION



ELECTRICAL

incl. driver
220 - 240 V
system 4.9 W
Class 1

PHYSICAL

diameter 26 mm
height 117 mm
0.24 kg

^a Colour may deviate slightly due to production conditions.

**CONE DIAGRAM**

standard 30°

h (m)	E0° (lx)	ø (m)
1	954	0.54
2	238	1.09
3	106	1.63
4	60	2.18
5	38	2.72