




PROJECT

TYPE


NOTES

QUANTITY

DATE



Round ceiling recessed downlight made from die-cast aluminium; adjustable; with trim; surface Aluminium Brushed; RAL 9006; inner ring black; installation without tools using blade springs; suitable for ceiling thickness of min. 2 mm; recessed depth 60 mm; with COB (Chip on Board) technology for maximum efficiency; light colour 3000 K; CRI ≥ 90; beam angle 31°; 360° rotatable and 35° tiltable; degree of protection IP20; Class 3; driver not included; optional honeycomb louver available, to reduce glare;



LUMINAIRE

Ceiling
 Recessed
 tilt max 35 °
 rotation 360 °
 Aluminium Brushed
 RAL 9006 ^a
 IP20
 Interior
 440 lm

LED Module

3000 K
 CRI ≥ 90
 L80 / 50000h
 ≤ 2 SDCM (initial MacAdam)

Optical

beam angle 31°

Electrical

excl. driver
 18 V
 system 5.0 W
 Class III
 Standard

Physical

diameter 76 mm
 height 35 mm
 0.12 kg
 blade springs

Cutout

diameter 68-70 mm
 min. ceiling thickness 2 mm
 max. ceiling thickness 25 mm
 recessed depth 60 mm

^a Colour may deviate slightly due to production conditions

[198161L5] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.



ELECTRICAL ACCESSORIES

Driver

Type	Colour	Voltage	L·W·H (MM)	Item number
5W 250mA 12-21V phase-cut dim		12-21V	68-33-22	90226201
10W 250mA 10-40V DALI-2 push dim		10-40V	166-29-21	90246403

OPTICAL ACCESSORIES

Honeycomb Louver

Type	Colour	Voltage	Ø (MM)	Item number
BLIEK petit CENO LECA PIRRO QITO	Black		29	915230B0

[198161L5] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.