




**PROJECT** \_\_\_\_\_

**TYPE** \_\_\_\_\_

**NOTES** \_\_\_\_\_

**QUANTITY** \_\_\_\_\_

**DATE** \_\_\_\_\_



Rectangular ceiling surface mounted downlight made from die-cast aluminium; rounded edges; with 2 spotlights; adjustable; surface Bronze Brushed; with COB (Chip on Board) technology for maximum efficiency; phase-cut dim; light colour 2700 K; CRI ≥ 90; beam angle 31°; spotlight heads 350° rotatable and 35° tiltable; degree of protection IP20; Class 1; driver included; optional honeycomb louver available, to reduce glare;

**LUMINAIRE**

Ceiling \_\_\_\_\_

Surface \_\_\_\_\_

tilt max 35 ° \_\_\_\_\_

rotation 350 ° \_\_\_\_\_

Bronze Brushed \_\_\_\_\_

IP20 \_\_\_\_\_

Interior \_\_\_\_\_

420 lm \_\_\_\_\_

**LED Module**

2700 K \_\_\_\_\_

CRI ≥ 90 \_\_\_\_\_

L80 / 50000h \_\_\_\_\_

≤ 2 SDCM (initial MacAdam) \_\_\_\_\_

**Optical**

beam angle 31° \_\_\_\_\_

**Electrical**

phase-cut dim \_\_\_\_\_

220 - 240 V \_\_\_\_\_

system 11.0 W \_\_\_\_\_

Class I \_\_\_\_\_

Standard \_\_\_\_\_

**Physical**


length 184 mm \_\_\_\_\_

width 80 mm \_\_\_\_\_

height 46 mm \_\_\_\_\_

0.6 kg \_\_\_\_\_

surface \_\_\_\_\_



[198664Q3] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.

198664Q3



**OPTICAL ACCESSORIES**

**Honeycomb Louver**

**Type**

BLIEK petit | CENO | LECA | PIRRO | QITO

**Colour**

Black

**Voltage**

**Ø (MM)**

29

**Item number**

915230B0