



PROJECT

---

TYPE

---

NOTES

---

QUANTITY


---

DATE

---



Round ceiling recessed downlight made from ASA; surface Black; No matching RAL; 3D printed by IQ LUX; installation without tools using blade springs; suitable for ceiling thickness of min. 8 mm; recessed depth 85 mm; beam angle 41°; with COB (Chip on Board) technology for maximum efficiency; light colour 2700 K; CRI ≥ 90; degree of protection IP20; Class 3; driver not included;



**LUMINAIRE**

Ceiling \_\_\_\_\_  
 Recessed \_\_\_\_\_  
 Black \_\_\_\_\_  
 No matching RAL \_\_\_\_\_  
 IP20 \_\_\_\_\_  
 Interior \_\_\_\_\_  
 360 lm \_\_\_\_\_

**LED Module**

2700 K \_\_\_\_\_  
 CRI ≥ 90 \_\_\_\_\_  
 L80 / 50000h \_\_\_\_\_  
 ≤ 3 SDCM (initial MacAdam) \_\_\_\_\_

**Optical**

Medium \_\_\_\_\_  
 beam angle 41° \_\_\_\_\_

**Electrical**

excl. driver \_\_\_\_\_  
 18 V \_\_\_\_\_  
 system 3.0 W \_\_\_\_\_  
 Class III \_\_\_\_\_  
 Standard \_\_\_\_\_

**Physical**

diameter 80 mm \_\_\_\_\_  
 height 61 mm \_\_\_\_\_  
 0.04 kg \_\_\_\_\_  
 blade springs \_\_\_\_\_

**Cutout**

diameter 74-76 mm \_\_\_\_\_  
 min. ceiling thickness 8 mm \_\_\_\_\_  
 recessed depth 85 mm \_\_\_\_\_

[199151B3] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.



**ELECTRICAL ACCESSORIES**

**Driver**

| Type                                  | Colour | Voltage | L·W·H (MM) | Item number |
|---------------------------------------|--------|---------|------------|-------------|
| 10W   200mA   30-42V   phase-cut dim  |        | 30-42V  | 85-22-41   | 90226402    |
| 8W   200mA   10-40V   DALI-2 push dim |        | 10-40V  | 166-29-21  | 90246302    |