



PROJECT _____

TYPE _____


NOTES _____

QUANTITY _____

DATE _____



Round ceiling recessed downlight made from ASA; surface Black; No matching RAL; 3D printed by IQ LUX; installation without tools using blade springs; suitable for ceiling thickness of min. 8 mm; recessed depth 77 mm; beam angle 13°; with COB (Chip on Board) technology for maximum efficiency; light colour 3000 K; CRI ≥ 90; degree of protection IP20; Class 3; driver not included;



LUMINAIRE

Ceiling _____
 Recessed _____
 Black _____
 No matching RAL _____
 IP20 _____
 Interior _____
 800 lm _____

LED Module

3000 K _____
 CRI ≥ 90 _____
 L80 / 80000h _____
 ≤ 3 SDCM (initial MacAdam) _____

Optical

Narrow _____
 beam angle 13° _____

Electrical

excl. driver _____
 36 V _____
 system 6.0 W _____
 Class III _____
 Standard _____

Physical

diameter 95 mm _____
 height 66 mm _____
 0.07 kg _____
 blade springs _____

Cutout

diameter 85-87 mm _____
 min. ceiling thickness 8 mm _____
 recessed depth 77 mm _____



ELECTRICAL ACCESSORIES

Driver

Type	Colour	Voltage	L·W·H (MM)	Item number
7.5W 180mA 27-42V phase-cut dim		27-42V	68-33-22	90226202
7.2W 180mA 10-40V DALI-2 push dim		10-40V	166-29-21	90246301