




PROJECT _____

TYPE _____


NOTES _____

QUANTITY _____

DATE _____



Round ceiling recessed downlight made from ASA; surface Silk Grey; adjustable; 3D printed by IQ LUX; installation without tools using blade springs; suitable for ceiling thickness of min. 8 mm; recessed depth 85 mm; beam angle 40°; with COB (Chip on Board) technology for maximum efficiency; light colour 2700 K; CRI ≥ 90; degree of protection IP20; Class 3; driver not included;



LUMINAIRE

Ceiling _____
 Recessed _____
 tilt max 21° _____
 rotation 360° _____
 Silk Grey _____
 IP20 _____
 Interior _____
 780 lm _____

LED Module

2700 K _____
 CRI ≥ 90 _____
 L80 / 50000h _____
 ≤ 3 SDCM (initial MacAdam) _____

Optical

Medium _____
 beam angle 40° _____

Electrical

excl. driver _____
 36 V _____
 system 6.0 W _____
 Class III _____
 Standard _____

Physical

diameter 94 mm _____
 height 60 mm _____
 0.09 kg _____
 blade springs _____

Cutout

diameter 85-87 mm _____
 min. ceiling thickness 8 mm _____
 recessed depth 85 mm _____

[199451SG3] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.



ELECTRICAL ACCESSORIES

Driver

Type	Colour	Voltage	L·W·H (MM)	Item number
7.5W 180mA 27-42V phase-cut dim		27-42V	68·33·22	90226202
7.2W 180mA 10-40V DALI-2 push dim		10-40V	166·29·21	90246301