




PROJECT

TYPE

NOTES

QUANTITY

DATE



Round ceiling suspended luminaire made from aluminium; hand blown glass in Frosted Diamond; inclusive adjustable cable suspension max. 2500mm in Signal Black; with COB (Chip on Board) technology for maximum efficiency; phase-cut dim; light colour 2700 K; binning initial MacAdam ≤ 2 SDCM; CRI ≥ 90 ; 220 - 240 V; degree of protection IP20; Class 2; driver included; light source replaceable by Wever & Ducré or by a professional with explicit authorization; control gear replaceable by end-user;

Luminaire

Ceiling
Suspended
Frosted Diamond
IP20
Interior
360 lm

Module

2700 K
CRI ≥ 90
L80 / 50000h
initial MacAdam ≤ 2 SDCM
358 lm
44 lm/W ^a

Optical

CIE flux code: 26 50 75 67 100

Electrical


phase-cut dim
220 - 240 V
system 8.2 W
Class 2

Physical

diameter 120 mm
height 128 mm
0.48 kg

^a datasheet.footnote.no-electrical-losses

LIGHT DISTRIBUTION



[238284FD3] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.