



PROJECT _____

TYPE _____

NOTES _____

QUANTITY _____

DATE _____



LUMINAIRE

Ceiling _____

Suspended _____

Champagne _____

IP20 _____

Interior _____

1460 lm _____

LED Module

3000 K _____

CRI \geq 90 _____

L80 / 50000h _____

\leq 3 SDCM (initial MacAdam) _____

Electrical

incl. driver _____

220 - 240 V _____

system 16.0 W _____

Class I _____

Standard _____

Physical

diameter 40 mm _____


height 1555 mm _____

1.76 kg _____

cable length max. 2500 mm _____



Slim, vertically oriented tubular pendant luminaire made of ribbed glass; aluminium end caps in Champagne; inclusive adjustable cable suspension max. 2500mm; light colour 3000 K; CRI \geq 90; CRI (Colour Rendering Index) \geq 90; 220 - 240 V; degree of protection IP20; Class 1; driver included;



[249384M5] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.