




PROJECT

TYPE

NOTES

QUANTITY

DATE



Suspended luminaire in an elongated capsule shape made from opal polyethylene; rounded end caps made from aluminium in black; suspended vertically or horizontally; inclusive cable suspension max. 2500 mm; light colour: tunable white diodes (2700-5000 K); CRI ≥ 90; PCB; 220 - 240 V; degree of protection IP20; Class 1; driver included; light source replaceable by Wever & Ducré or by a professional with explicit authorization; control gear replaceable by end-user;

LUMINAIRE

Ceiling
Suspended
Opal White + Black
IP20
Interior
1250 lm

LED Module

tunable white
2700 - 5000 K
CRI ≥ 90
≤ 3 SDCM (initial MacAdam)

Optical


Opal

Electrical

DALI-2 DT8
220 - 240 V
system 16.0 W
Class I
Standard

Physical

Black ceiling base
diameter 200 mm
height 557 mm
2 kg
cable length max. 2500 mm



[‘251185B9’] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.