



PROJECT

TYPE

NOTES

QUANTITY

DATE



LUMINAIRE

Ceiling _____
 Suspended _____
 Opal White + Black _____
 IP20 _____
 Interior _____
 4500 lm _____

LED Module

tunable white _____
 2700 - 5000 K _____
 CRI ≥ 90 _____
 ≤ 3 SDCM (initial MacAdam) _____

Optical


Opal _____

Electrical


DALI-2 DT8 _____
 220 - 240 V _____
 system 35 W _____
 Class I _____
 Standard _____

Physical

Black ceiling base _____
 diameter 200 mm _____
 height 1754 mm _____
 4.4 kg _____
 cable length max. 2500 mm _____



Suspended luminaire in an elongated capsule shape made from opal polyethylene; rounded end caps made from aluminium in black; suspended vertically or horizontally; inclusive cable suspension max. 2500 mm; light colour: tunable white diodes (2700-5000 K); CRI ≥ 90; PCB; 220 - 240 V; degree of protection IP20; Class 1; driver included; light source replaceable by Wever & Ducré or by a professional with explicit authorization; control gear replaceable by end-user;



[‘251385B9’] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.