



PROJECT

TYPE

NOTES

QUANTITY

DATE



Ring shaped suspended luminaire made from die-cast aluminium; inclusive adjustable cable suspension max. 4000mm and base in Signal Black; surface Bronze; wet painted, matt smooth; RAL 7013; silicone cover; PCB 3-step binning; phase-cut dim; light colour 2700 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90 ; 220 - 240 V; degree of protection IP20; Class 2; driver included; light source replaceable by Wever & Ducré or by a professional with explicit authorization; control gear replaceable by end-user;

Luminaire

Ceiling
Suspended
Bronze
RAL 7013 ^a
IP20
Interior
760 lm

Module

2700 K
L80 / 100000h
1349 lm
169 lm/W ^b

Optical

Opal
CIE flux code: 23 50 78 50 100



Electrical

phase-cut dim
220 - 240 V
system 10.7 W
Class 2

Physical

diameter 380 mm
height 25 mm
0.59 kg

LIGHT DISTRIBUTION



[271182Q3] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.