



**PROJECT**

**TYPE**


**NOTES**

**QUANTITY**

**DATE**



Rectangular wall recessed luminaire made from aluminium; surface Black Matt; powder coated; matt texture; RAL 9011; recessed depth 18 mm; suitable for wall thickness of 8-18mm; PCB 3-step binning; 24 V; light colour 3000 K; CRI  $\geq 90$ ; degree of protection IP20; Class 3; driver not included;



**Luminaire**

Wall  
Recessed  
Black Matt  
RAL 9011<sup>a</sup>  
IP20  
Interior  
15 lm

**Module**

3000 K  
CRI  $\geq 90$   
 $\leq 3$  SDCM (initial MacAdam)

**Optical**

Asymetric

**Electrical**

excl. driver  
24 V  
system 2.0 W  
Class 3

**Physical**

length 140 mm  
width 22 mm  
height 16 mm  
0.04 kg

**Cutout**

length 135 mm  
width 9 mm  
min. ceiling thickness 8 mm  
max. ceiling thickness 18 mm  
recessed depth 18 mm

<sup>a</sup> Colour may deviate slightly due to production conditions

3058A1B5



**ELECTRICAL ACCESSORIES**

| Driver<br>Type            | Colour | Voltage | L·W·H (MM) | Item number |
|---------------------------|--------|---------|------------|-------------|
| 25W   24V   phase-cut dim |        | 24V     | 128·52·30  | 90222701    |