



317478G3

国数数全国
A. C. C.

PROJECT TYPE NOTES QUANTITY





DATE



Square shaped wall surface luminaire made from aluminium; Gold wet painted; brushed; PCB 3-step binning; phase-cut dim; light colour 2700 K; binning initial MacAdam \leq 3 SDCM; CRI \geq 90; 220 - 240 V; degree of protection IP20; Class 2; light source replaceable by Wever & Ducré or by a professional with explicit authorization;

38-43

Luminaire

Wall	
Surface	
Gold	
IP20	
Interior	
415 lm	

Module

2700 K		
CRI ≥ 90		
L80 / 70000 h		
initial MacAdam ≤ 3 SDCM		
413 lm		
49 lm/W ^a		

Optical

CIE flux code: 0 2 28 22 100

Electrical


phase-cut dim
220 - 240 V
system 8.5 W
Class 2

Physical

length 220 mm		
width 220 mm		
height 38 mm		
1.01 kg		

^a Without electrical losses

LIGHT DISTRIBUTION



^{[&#}x27;317478G3'] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.