



PROJECT

TYPE


NOTES

QUANTITY

DATE



Rectangular wall recessed luminaire made from aluminium; surface Black Matt; powder coated; matt texture; RAL 9011; recessed depth 40 mm; suitable for ceiling thickness of min. 12 mm; PCB 3-step binning; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90 ; degree of protection IP20; Class 3; driver not included; light source not replaceable;



Luminaire

Wall
Recessed
Black Matt
RAL 9011^a
IP20
Interior
30 / 50 lm

Module

3000 K
CRI ≥ 90
L70 / 60000h
initial MacAdam ≤ 3 SDCM

Optical

Asymetric
CIE flux code: 52 75 88 75 100

Electrical

excl. driver
6 V
Class 3

Physical



length 65 mm
width 33 mm
height 200 mm
0.28 kg

Cutout

length 47 mm
width 182 mm
min. ceiling thickness 12 mm
recessed depth 40 mm

^a datasheet.footnote.ral_footnote

LIGHT DISTRIBUTION





MOUNTING ACCESSORIES

Concrete Housing

Type	Colour	Voltage	L·W·H (MM)	Item number
ORIS 0.7 RETO 2.0			57-55-190	90012044

Recessed Housing incl. plasterkit

Type	Colour	Voltage	L·W·H (MM)	Item number
ORIS 0.7 RETO 2.0			100-67-250	90012039

ELECTRICAL ACCESSORIES

Driver

Type	Colour	Voltage	L·W·H (MM)	Item number
6W 350mA 3-22V		3-22V	68-35-21	90213202
6W 700mA 3-8.4V		3-8,4V	68-35-21	90215203