




PROJECT

TYPE


NOTES

QUANTITY

DATE



Rectangular wall recessed luminaire made from aluminium; surface Black Matt; powder coated; matt texture; RAL 9011; recessed depth 40 mm; suitable for ceiling thickness of min. 12 mm; PCB 3-step binning; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90 ; degree of protection IP20; Class 3; driver not included; light source not replaceable;



Luminaire

Wall
Recessed
Black Matt
RAL 9011 ^a
IP20
Interior
44 / 75 lm

Module

3000 K
CRI ≥ 90
L70 / 60000h
initial MacAdam ≤ 3 SDCM

Optical

Asymmetric
CIE flux code: 41 77 91 85 100

Electrical

excl. driver
6 V
Class 3

Physical


length 80 mm
width 33 mm
height 80 mm
0.15 kg

Cutout

length 66 mm
width 66 mm
min. ceiling thickness 12 mm
recessed depth 40 mm

^a datasheet.footnote.ral_footnote

LIGHT DISTRIBUTION





MOUNTING ACCESSORIES

Concrete Housing

Type	Colour	Voltage	L·W·H (MM)	Item number
ORIS 0.8 RETO 0.8			69-69-61	90012046

Recessed Housing incl. plasterkit

Type	Colour	Voltage	L·W·H (MM)	Item number
ORIS 0.8 RETO 0.8			109-109-74	90012047

ELECTRICAL ACCESSORIES

Driver

Type	Colour	Voltage	L·W·H (MM)	Item number
6W 350mA 3-22V		3-22V	68-35-21	90213202
6W 700mA 3-8.4V		3-8,4V	68-35-21	90215203