



## PROJECT

## TYPE


## NOTES

## QUANTITY

## DATE



Tubular wall surface luminaire made from aluminium; surface Black Matt; powder coated, matt texture; RAL 9011; up and down light emission; with COB (Chip on Board) technology for maximum efficiency; phase-cut dim; light colour 2700 K; binning initial MacAdam  $\leq 2$  SDCM; CRI  $\geq 90$ ; beam angle  $23^\circ$ ; 220 - 240 V; degree of protection IP20; Class 1; UGR  $\leq 10$ ; VDU compatible workplace luminaire according to DIN EN 12464-1; luminance above  $65^\circ \leq 1500$  cd/m<sup>2</sup>; driver included; light source replaceable by Wever & Ducré or by a professional with explicit authorization; control gear replaceable by end-user;



## GENERAL

Wall  
Surface  
Black Matt  
RAL 9011<sup>a</sup>  
IP20  
Interior  
indirect 795 lm  
direct 795 lm  
total 1590 lm  
CIE flux code: 100 100 100 52 100


## LED

2700 K  
CRI  $\geq 90$   
L80 / 50000h  
initial MacAdam  $\leq 2$  SDCM

## OPTICAL

Standard  
beam angle  $23^\circ$

## LIGHT DISTRIBUTION



## ELECTRICAL

phase-cut dim  
220 - 240 V  
system 22.8 W  
Class 1

## PHYSICAL

length 71 mm  
width 47 mm  
height 720 mm  
0.96 kg

<sup>a</sup> Colour may deviate slightly due to production conditions.