

DOMINO 1.0

LIGHT DISTRIBUTION

960

cd

C0/C180

C90/C270

180

0°

150°

30

.120°

. 60°

90

3371A4B2



PROJECT			
ТҮРЕ			
NOTES			
QUANTITY			
DATE			





Wall surface luminaire made from aluminium; surface Black Matt; powder coated; matt texture; RAL 9011; PCB 3-step binning; phase-cut dim; light colour 2700 K; binning initial MacAdam \leq 3 SDCM; CRI \geq 80; 220 - 240 V; degree of protection IP20; Class 1; driver included; light source not replaceable; control gear replaceable by end-user;

GENERAL

Wall
Surface
Black Matt
RAL 9011 ^a
IP20
Interior
1190 lm
CIE flux code: 37 64 82 0 100

LED

2700 K CRI ≥ 80 L80 / 60000h initial MacAdam \leq 3 SDCM

OPTICAL

Asymetric

ELECTRICAL

phase-cut dim 220 - 240 V system 13.7 W Class 1

PHYSICAL

length 180 mm	
width 78 mm	
height 30 mm	_
0.69 kg	_

^a Colour may deviate slightly due to production conditions.



['3371A4B2'] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.

© Wever & Ducré BV · Spinnerijstraat 99/21 · 8500 Kortrijk · Belgium · www.weverducre.com