

339220BB1

PROJECT

TYPE

NOTES

QUANTITY

DATE










Wall surface luminaire made from aluminium; surface Black Matt wet painted; matt texture; RAL 9011; shade Black Matt; wet painted; matt texture; cable base round; lamp socket GU10; lamp type PAR16; max. 15W; 100 - 240 V; degree of protection IP20; Class 1; lamp not included;



GENERAL

| Wall |
|-----------------------|
| Surface |
| tilt max 45 ° |
| rotation 30 ° |
| Mounting: Black Matt |
| RAL 9011 ^a |
| Shade Black Matt |
| IP20 |
| Interior |

LED

| lamp PAR16 |
|------------------------|
| socket GU10 |
| max. per socket 15.0 W |
| CRI ≥ 90 |

OPTICAL

Shade 1.0

ELECTRICAL

100 - 240 V Class 1

PHYSICAL

| diameter 205 mm |
|------------------|
| height 382 mm |
| 1.29 kg |
| cable base round |
| • |


^a Colour may deviate slightly due to production conditions.


MEASURED LAMPS

| PAR16 LAMP 3000K CRI90 | |
|------------------------|--|
| 465 lm | |
| 6.5 W | |
| | |

PAR16 LAMP 2700K CRI90 445 lm 6.5 W

LIGHT DISTRIBUTION





^{[&#}x27;339220BB1'] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.



ROOMOR WALL 3.1

339220BB1



ELECTRICAL ACCESSORIES

LED LAMPS

| Type | Colour | Voltage | Item number |
|------|---------------|---------|-------------|
| | Black Texture | | W901228B3 |
| | Black Texture | | W901228B5 |

LAMPS

PAR16 LED Lamp

| Туре | Colour | Voltage | Ø·H (MM) | Item number |
|------------------------|--------|---------|----------|-------------|
| 2700K >90 CRI GU10 | White | | 50.60 | 901228W3 |
| 3000K >90 CRI GU10 | White | | 50-60 | 901228W5 |
| 2700K >80 CRI GU10 | Silver | | 50.60 | 905227S2 |
| 3000K >80 CRI GU10 | Silver | | 50.60 | 905227S4 |