



**PROJECT**

**TYPE**

**NOTES**

**QUANTITY**

**DATE**



Round wall surface luminaire made from aluminium; indirect light distribution; surface Black Matt; powder coated, matt texture; RAL 9011; opal PMMA diffuser; PCB 3-step binning; phase-cut dim; light colour 2700 K; binning initial MacAdam  $\leq 3$  SDCM; CRI  $\geq 90$ ; 220 - 240 V; degree of protection IP20; Class 1; driver included; optional spacer available for overlapping; light source replaceable by Wever & Ducré or by a professional with explicit authorization; control gear replaceable by end-user;

**GENERAL**

Wall  
Surface  
Black Matt  
RAL 9011<sup>a</sup>  
IP20  
Interior  
1180 lm  
CIE flux code: 12 36 67 50 100

**LED**

2700 K  
CRI  $\geq 90$   
L80 / 50000h  
initial MacAdam  $\leq 3$  SDCM

**OPTICAL**

Opal



**ELECTRICAL**

phase-cut dim  
220 - 240 V  
system 13.2 W  
Class 1

**PHYSICAL**

length 400 mm  
width 115 mm  
height 400 mm  
0.32 kg

**LIGHT DISTRIBUTION**



[371184B3] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of  $\pm 10\%$ , those for the electrical connected load are initially subject to a tolerance of  $\pm 10\%$ , and those for the colour temperature are initially subject to a tolerance of  $\pm 150$  K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.



## Maintenance Factor

Operating Time [h]	10.000	20.000	30.000	40.000	50.000
LLMF	0.98	0.97	0.95	0.93	0.92
LSF	1	1	1	1	1

MF LMF × RSMF × LLMF × LSF

MF Maintenance Factor

LMF<sup>a</sup> Luminaire Maintenance Factor

RSMF<sup>a</sup> Room Surface Maintenance Factor

LLMF Lamp Lumens Maintenance Factor

LSF Lamp Survival Factor

<sup>a</sup>According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

## MOUNTING ACCESSORIES

### Wall-/Base-Spacer

Type	Colour	Voltage	L·W·H (MM)	Item number
FINLIN ROUND	Black		52·30·23	900196B0