



PROJECT

TYPE


NOTES

QUANTITY

DATE



Round outdoor floor or wall projector; surface Anthracite Grey; powder coated; matt texture; RAL 7016; with COB (Chip on Board) technology for maximum efficiency; phase-cut dim; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 80 ; 220 - 240 V; 110° tiltable; beam angle 100°; degree of protection IP65; Class 2; driver included; optional ground spike available; optional snoot in Black Matt available; light source not replaceable; control gear replaceable by end-user;



Luminaire

Floor
Standing
tilt max 110°
Anthracite Grey
RAL 7016^a
IP65
Exterior
1520 lm
1520 lm

Module

3000 K
CRI ≥ 80
L80 / 60000h
initial MacAdam ≤ 3 SDCM
1520 lm
64 lm/W

Optical

Extreme wide
beam angle 100°
UGR ≤ 10
 $\geq 65^\circ < 1500 \text{ cd/m}^2$
CIE flux code: 0 0 0 0 100


Electrical

phase-cut dim
220 - 240 V
system 23.7 W
Class 2

Physical

diameter 160 mm
height 35 mm
1.41 kg

LIGHT DISTRIBUTION



^a Colour may deviate slightly due to production conditions.



BASE

Ground Spike

Type	Colour	Voltage	Ø-H (MM)	Item number
X-BEAM			43-212	90013115

OPTICAL ACCESSORIES

Snoot round

Type	Colour	Voltage	Ø-W (MM)	Item number
X-BEAM	Black		166-45	90019031