



PROJECT

TYPE

NOTES

QUANTITY

DATE



IP44



Round shape ceiling surface luminaire made from die-cast aluminium; surface White Matt; powder coated; matt texture; RAL 9010; opal PMMA cover; PCB 3-step binning; phase-cut dim; light colour 2700 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90 ; degree of protection IP44; Class 1; light source replaceable by Wever & Ducré or by a professional with explicit authorization;

Luminaire

Ceiling
Surface
White Matt
RAL 9010 ^a
IP44
Interior
3340 lm

Module

2700 K
CRI ≥ 90
L80 / 60000h
initial MacAdam ≤ 3 SDCM
3955 lm
124 lm/W ^b

Optical

CIE flux code: 45 76 94 95 100



Electrical

phase-cut dim
220 - 240 V
system 32 W
Class 1

Physical

diameter 345 mm
height 64 mm
1.9 kg

LIGHT DISTRIBUTION



[701388W3] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.

**ELECTRICAL ACCESSORIES**

Dimmer Type	Colour	Voltage	L·W·H (MM)	Item number
for switch		230V	46·17.5·46	90019017
DIN RAIL	White	230V	17·55·90	90019018