



PROJECT

TYPE

NOTES

QUANTITY


DATE



IP65




Rectangular wall surface luminaire made from aluminium; rounded edges; surface Anthracite Grey; powder coated; matt texture; RAL 7016; up and down light emission; PCB; phase-cut dim; light colour 2700 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90 ; 220 - 240 V; degree of protection IP65; Class 1; driver included; light source not replaceable; control gear replaceable by end-user;



DATASHEET.QUICKSUM.LUMINAIRE LIGHT DISTRIBUTION

Wall
Surface
Anthracite Grey
RAL 7016^a
IP65
Exterior
indirect 495 lm
direct 495 lm
total 990 lm



DATASHEET.QUICKSUM.MODULE

2700 K
CRI ≥ 90
L80 / 50000h
initial MacAdam ≤ 3 SDCM
990 lm
80 lm/W

DATASHEET.QUICKSUM.OPTICAL

CIE flux code: 57 86 98 50 100

DATASHEET.QUICKSUM.ELECTRICAL

phase-cut dim
220 - 240 V
system 12.3 W
Class 1

DATASHEET.QUICKSUM.PHYSICAL

length 150 mm
width 40 mm
height 60 mm
0.5 kg

^a Colour may deviate slightly due to production conditions.


Maintenance Factor

Operating Time [h]	10.000	20.000	30.000	40.000	50.000
LLMF	0.98	0.96	0.94	0.93	0.91
LSF	1	1	1	1	1

MF	$LMF \times RSMF \times LLMF \times LSF$	RSMF ^a	Room Surface Maintenance Factor
MF	Maintenance Factor	LLMF	Lamp Lumens Maintenance Factor
LMF ^a	Luminaire Maintenance Factor	LSF	Lamp Survival Factor

^aAccording to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.