



PROJECT

TYPE


NOTES

QUANTITY

DATE



Floor surface mounted luminaire made from die-cast aluminium; surface Anthracite Grey; powder coated; matt texture; RAL 7016; down light emission; PCB; phase-cut dim; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90 ; 220 - 240 V; degree of protection IP65; Class 1; driver included; fixation base not included; optional ground fixation available; light source not replaceable; control gear not replaceable;



Luminaire

Floor
Surface
Anthracite Grey
RAL 7016 ^a
IP65
Exterior
1130 lm
1130 lm


Module

3000 K
CRI ≥ 90
L80 / 50000h
initial MacAdam ≤ 3 SDCM
1126 lm
62 lm/W

Optical

CIE flux code: 50 81 97 100 100

LIGHT DISTRIBUTION



Electrical

phase-cut dim
220 - 240 V
system 18.3 W
Class 1

Physical

length 133 mm
width 148 mm
height 52 mm
0.65 kg

^a Colour may deviate slightly due to production conditions.


Maintenance Factor

Operating Time [h]	10.000	20.000	30.000	40.000	50.000
LLMF	0.98	0.96	0.94	0.93	0.91
LSF	1	1	1	1	1

MF	LMF × RSMF × LLMF × LSF	RSMF ^a	Room Surface Maintenance Factor
MF	Maintenance Factor	LLMF	Lamp Lumens Maintenance Factor
LMF ^a	Luminaire Maintenance Factor	LSF	Lamp Survival Factor

^aAccording to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

BASE
Ground Fixation Plate

Type	Colour	Voltage	Ø·H (MM)	Item number
KIOSK SWAM			80·10	90019019

Pole 400 straight

Type	Colour	Voltage	Length (MM)	Item number
KIOSK	Anthracite Grey		400	910101A0
KIOSK	Bronze		400	910101Q0

Pole 600 straight

Type	Colour	Voltage	Length (MM)	Item number
KIOSK	Anthracite Grey		600	910102A0
KIOSK	Bronze		600	910102Q0

Pole 800 straight

Type	Colour	Voltage	Length (MM)	Item number
KIOSK	Anthracite Grey		800	910103A0
KIOSK	Bronze		800	910103Q0