



PROJECT

TYPE

NOTES

QUANTITY


DATE



IP65



Rectangular wall recessed luminaire made from aluminium; surface Grey Texture; powder coated; matt texture; RAL 9007; recessed depth 40 mm; suitable for ceiling thickness of min. 12 mm; PCB 3-step binning; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90 ; degree of protection IP65; Class 3; driver not included; light source not replaceable;



Luminaire

Wall
Recessed
Grey Texture
RAL 9007 ^a
IP65
Exterior
83 lm / 350mA
140 lm / 700mA

Module

3000 K
CRI ≥ 90
L70 / 60000h
initial MacAdam ≤ 3 SDCM
83 lm / 350mA
27 lm/W ^b
6.5 W ^b

Optical

Asymmetric
CIE flux code: 49 78 91 83 100

Electrical

excl. driver
9 V
Class 3

Physical

length 130 mm
width 33 mm
height 200 mm
0.42 kg



Cutout

length 115 mm
width 185 mm
min. ceiling thickness 12 mm
recessed depth 40 mm

^a datasheet.footnote.ral_footnote

^b datasheet.footnote.no-electrical-losses

LIGHT DISTRIBUTION





MOUNTING ACCESSORIES

Concrete Housing

Type	Colour	Voltage	L·W·H (MM)	Item number
ORIS 2.0			122-55-190	90012042

Recessed Housing incl. plasterkit

Type	Colour	Voltage	L·W·H (MM)	Item number
ORIS 2.0			160-67-250	90012043

ELECTRICAL ACCESSORIES

Driver

Type	Colour	Voltage	L·W·H (MM)	Item number
3W 350 mA 3-15V IP66		3-15V	52-30-23	90213101
7W 500mA 5-14.5V IP67		5-14.5V	57-41-24	90214301
7W 700mA 3-10.5V IP67		3-10,5V	57-41-24	90215301