



PROJECT

TYPE

NOTES

QUANTITY


DATE



IP65



Floor surface mounted luminaire made from die-cast aluminium; surface Anthracite Grey; powder coated; matt texture; RAL 7016; with COB (Chip on Board) technology for maximum efficiency; phase-cut dim; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90 ; 220 - 240 V; degree of protection IP65; Class 1; optional ground spike available; fixation base not included; light source not replaceable;



Luminaire

Floor
Standing
Anthracite Grey
RAL 7016 ^a
IP65
Exterior
215 lm
215 lm


Module

3000 K
CRI ≥ 90
L70 / 50000 h
initial MacAdam ≤ 3 SDCM
216 lm
31 lm/W

Optical

Asymetric
CIE flux code: 51 89 97 98 100

LIGHT DISTRIBUTION



Electrical

phase-cut dim
220 - 240 V
system 6.9 W
Class 1

Physical

length 70 mm
width 70 mm
height 150 mm
0.69 kg

^a Colour may deviate slightly due to production conditions.



Maintenance Factor

Operating Time [h]	10.000	20.000	30.000	40.000	50.000
LLMF	0	0	0	0	0
LSF	1	1	1	1	1

MF	LMF × RSMF × LLMF × LSF	RSMF ^a	Room Surface Maintenance Factor
MF	Maintenance Factor	LLMF	Lamp Lumens Maintenance Factor
LMF ^a	Luminaire Maintenance Factor	LSF	Lamp Survival Factor

^aAccording to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

BASE

Concrete Ground Fixation

Type	Colour	Voltage	L·W·H (MM)	Item number
LINUS			112-112-359	90013302

Ground Spike

Type	Colour	Voltage	L·W·H (MM)	Item number
LINUS			112-112-357	90013103

Pole 150

Type	Colour	Voltage	L·W·H (MM)	Item number
LINUS	Anthracite Grey		112-112-150	910024A0
LINUS	Dark Grey Texture		112-112-150	910024D0
LINUS	Bronze		112-112-150	910024Q0

Pole 350

Type	Colour	Voltage	L·W·H (MM)	Item number
LINUS	Anthracite Grey		112-112-350	910026A0
LINUS	Dark Grey Texture		112-112-350	910026D0
LINUS	Bronze		112-112-350	910026Q0

Pole 550

Type	Colour	Voltage	L·W·H (MM)	Item number
LINUS	Anthracite Grey		112-112-550	910028A0
LINUS	Dark Grey Texture		112-112-550	910028D0
LINUS	Bronze		112-112-550	910028Q0