



PROJECT

TYPE

NOTES

QUANTITY

DATE



IP65



Squared ceiling surface mounted downlight made from die-cast aluminium; surface Anthracite Grey; powder coated; matt texture; RAL 7016; with COB (Chip on Board) technology for maximum efficiency; phase-cut dim; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90 ; 220 - 240 V; beam angle 32°; degree of protection IP65; Class 1; driver included; light source replaceable by Wever & Ducré or by a professional with explicit authorization; control gear replaceable by an authorized professional;

Luminaire

Ceiling
Surface
Anthracite Grey
RAL 7016 ^a
IP65
Exterior
720 lm

Module

3000 K
CRI ≥ 90
L80 / 100000 h
initial MacAdam ≤ 3 SDCM
722 lm
75 lm/W ^b

Optical

Standard
beam angle 32°
CIE flux code: 98 99 100 100 100



Electrical

phase-cut dim
220 - 240 V
system 9.6 W
Class 1

Physical

length 79 mm
width 79 mm
height 104 mm
0.74 kg

LIGHT DISTRIBUTION



^a datasheet.footnote.ral_footnote

^b datasheet.footnote.no-electrical-losses

**CONE DIAGRAM**

standard 38°

h (m)	E0° (lx)	ø (m)
1	1640	0.68
2	410	1.36
3	180	2.05
4	100	2.73
5	70	3.41