



PROJECT

TYPE

NOTES

QUANTITY


DATE



IP65



Square wall recessed luminaire made from aluminium; surface Bronze; powder coated; matt texture; RAL 075 30 10; recessed depth 40 mm; suitable for ceiling thickness of min. 12 mm; PCB 3-step binning; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90 ; degree of protection IP65; Class 3; driver not included; light source not replaceable;



Luminaire

Wall
Recessed
Bronze
RAL 075 30 10 ^a
IP65
Exterior
170 lm
170 lm

Module

3000 K
CRI ≥ 90
L80 / 50000h
initial MacAdam ≤ 3 SDCM
168 lm
34 lm/W

Optical

Asymmetric
CIE flux code: 60 86 97 99 100

Electrical

excl. driver
24 V
Class 3


Physical

length 130 mm
width 16 mm
height 130 mm
0.42 kg

Cutout

length 115 mm
width 117 mm
min. ceiling thickness 12 mm
recessed depth 40 mm

LIGHT DISTRIBUTION



^a Colour may deviate slightly due to production conditions.



MOUNTING ACCESSORIES

Concrete Housing

Type	Colour	Voltage	L·W·H (MM)	Item number
ORIS 1.3 RETO 1.3			120-55-120	90012040

Recessed Housing incl. plasterkit

Type	Colour	Voltage	L·W·H (MM)	Item number
ORIS 1.3 RETO 1.3			160-68-160	90012041

ELECTRICAL ACCESSORIES

Driver

Type	Colour	Voltage	L·W·H (MM)	Item number
35W 24V IP67		24V	175-31-43	90212802
100W 24V IP67		24V	178-68-39	90212903