



PROJECT

TYPE


NOTES

QUANTITY

DATE



Rectangular wall recessed luminaire made from aluminium; surface Anthracite Grey; powder coated; matt texture; RAL 7016; recessed depth 40 mm; suitable for ceiling thickness of min. 12 mm; PCB 3-step binning; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90 ; degree of protection IP65; Class 3; driver not included; light source not replaceable;



Luminaire

Wall
Recessed
Anthracite Grey
RAL 7016 ^a
IP65
Exterior
330 lm
330 lm

Module

3000 K
CRI ≥ 90
L80 / 50000h
initial MacAdam ≤ 3 SDCM
332 lm
49 lm/W

Optical

Asymmetric
CIE flux code: 58 85 97 99 100

Electrical

excl. driver
24 V
Class 3


Physical

length 200 mm
width 16 mm
height 80 mm
0.41 kg

Cutout

length 47 mm
width 182 mm
min. ceiling thickness 12 mm
recessed depth 40 mm

LIGHT DISTRIBUTION



^a Colour may deviate slightly due to production conditions.



MOUNTING ACCESSORIES

Concrete Housing

Type	Colour	Voltage	L·W·H (MM)	Item number
ORIS 0.7 RETO 2.0			57-55-190	90012044

Recessed Housing incl. plasterkit

Type	Colour	Voltage	L·W·H (MM)	Item number
ORIS 0.7 RETO 2.0			100-67-250	90012039

ELECTRICAL ACCESSORIES

Driver

Type	Colour	Voltage	L·W·H (MM)	Item number
35W 24V IP67		24V	175-31-43	90212802
100W 24V IP67		24V	178-68-39	90212903