


# RETO WALL SURFACE OUTDOOR 1.3

| PROJECT |  |  |  |
|---------|--|--|--|
| TYPE    |  |  |  |
| NOTES   |  |  |  |

DATE

QUANTITY












Squared wall surface mounted luminaire made from aluminium; surface Bronze; powder coated; matt texture; RAL 075 30 10; PCB 3-step binning; phase-cut dim; light colour 3000 K; binning initial MacAdam  $\leq$  3 SDCM; CRI  $\geq$  90; degree of protection IP65; Class 1; driver included; light source not replaceable; control gear replaceable by end-user;



#### Luminaire

| Wall                       |
|----------------------------|
| Surface                    |
| Bronze                     |
| RAL 075 30 10 <sup>a</sup> |
| IP65                       |
| Exterior                   |
| 160 lm                     |
|                            |

#### **LED Module**

| 3000 K                     |
|----------------------------|
| CRI ≥ 90                   |
| L80 / 50000h               |
| ≤ 3 SDCM (initial MacAdam) |
| 161 lm                     |
| 32 lm/W <sup>b</sup>       |

#### **Optical**

| Asymetric                   |  |
|-----------------------------|--|
| CIE flux code: 60 85 97 100 |  |
| 100                         |  |

## **Electrical**


| phase-cut dim |  |
|---------------|--|
| 220 - 240 V   |  |
| system 5.1 W  |  |
| Class 1       |  |

# **Physical**

| length 130 mm |
|---------------|
| width 36 mm   |
| height 130 mm |
| 0.62 kg       |
|               |

<sup>&</sup>lt;sup>a</sup> Colour may deviate slightly due to production conditions

## LIGHT DISTRIBUTION



<sup>&</sup>lt;sup>b</sup> Without electrical and optical losses