



PROJECT

TYPE

NOTES

QUANTITY


DATE



IP65




Cylindrical ceiling surface mounted downlight made from die-cast aluminium; surface Anthracite Grey; RAL 7016; with COB (Chip on Board) technology for maximum efficiency; phase-cut dim; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90 ; 220 - 240 V; degree of protection IP65; Class 1; light source not replaceable;



DATASHEET.QUICKSUM.LUMINAIRE LIGHT DISTRIBUTION

Ceiling
Surface
Anthracite Grey
RAL 7016 ^a
IP65
Exterior
555 lm
555 lm



DATASHEET.QUICKSUM.MODULE

3000 K
CRI ≥ 90
L70 / 55000h
initial MacAdam ≤ 3 SDCM
555 lm
93 lm/W

— C0/C180

DATASHEET.QUICKSUM.OPTICAL

Standard
beam angle 36°
CIE flux code: 96 99 100 100
100

DATASHEET.QUICKSUM.ELECTRICAL

phase-cut dim
220 - 240 V
system 6.0 W
Class 1

DATASHEET.QUICKSUM.PHYSICAL

diameter 50 mm
height 75 mm
0.24 kg

^a Colour may deviate slightly due to production conditions.

**CONE DIAGRAM**

standard 34°

h (m)	E0° (lx)	ø (m)
1	1300	0.62
2	330	1.23
3	140	1.85
4	80	2.46
5	50	3.08