



**PROJECT**

**TYPE**

**NOTES**

**QUANTITY**


**DATE**



IP67



Round floor recessed luminaire made from stainless steel and glass; asymmetric light beam; surface Inox; recessed depth 160 mm; with COB (Chip on Board) technology for maximum efficiency; phase-cut dim; light colour 3000 K; binning initial MacAdam  $\leq 3$  SDCM; CRI  $\geq 90$ ; degree of protection IP67; Class 2; driver not included; light source replaceable by Wever & Ducré or by a professional with explicit authorization;



**Luminaire**

Floor  
Recessed  
Inox  
IP67  
IK08  
Exterior  
565 lm  
565 lm

**Module**

3000 K  
CRI  $\geq 90$   
L70 / 55000h  
initial MacAdam  $\leq 3$  SDCM  
563 lm  
49 lm/W

**Optical**

Asymetric  
CIE flux code: 31 58 80 0 100

**Electrical**

phase-cut dim  
220 - 240 V  
system 11.4 W  
Class 2


**Physical**

diameter 120 mm  
height 113 mm  
1.06 kg

**Cutout**

recessed depth 160 mm

**LIGHT DISTRIBUTION**





## Maintenance Factor

Operating Time [h]	10.000	20.000	30.000	40.000	50.000
LLMF	0	0	0	0	0
LSF	1	1	1	1	1

MF	$LMF \times RSMF \times LLMF \times LSF$	RSMF <sup>a</sup>	Room Surface Maintenance Factor
MF	Maintenance Factor	LLMF	Lamp Lumens Maintenance Factor
LMF <sup>a</sup>	Luminaire Maintenance Factor	LSF	Lamp Survival Factor

<sup>a</sup>According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

## MOUNTING ACCESSORIES

### Ground Housing

Type	Colour	Voltage	Ø·H (MM)	Item number
MAP 1.2   CHART 1.2   MAP ASYM 1.2   CHART ASYM 1.2			185-150	90012203