

## Surface-mounted ceiling light - Can Tilt round, 2 x 7.5 W GU10, black




Image similar

### Prices

<b>List price</b> (VAT included)	84.95 EUR per 1
<b>Minimum order quantity</b>	1
<b>Order step</b>	1

### Information

<b>Order number</b>	348254
<b>EAN</b>	4042943182203
<b>Brand</b>	 <b>DEKOLIGHT</b>

### Description

- Flat and discreet lamp base
- Replaceable lamp to offer an individual lighting solution
- Can be customised with a wide range of accessories
- Can be combined with the comprehensive CAN series product family

The round CAN surface-mounted ceiling light provides a flexible lighting solution for commercial and private spaces. Available as a one-, two- and three-luminaire variant in the colours black and white, it enables precise alignment of the light using rotating and swivelling luminous elements. The widely used GU10 base enables quick and simple replacement of the lamp, while the screw-on cylinder housing enables tool-free access. Installation for rigid and flexible conductors is easy and efficient due to the integrated push terminals. The CAN surface-mounted ceiling light is part of a versatile series, which also contains pendant, wall, reading and outdoor lights.

### Features

<b>RRP incl. VAT</b>	84.95 EUR
<b>Housing Material</b>	Aluminium
<b>Housing Color</b>	Black
<b>Socket Quantity</b>	2 PCS
<b>max. Power</b>	2x max. 7.5 W
<b>Base height</b>	15 mm
<b>Base diameter</b>	200 mm
<b>Frequency</b>	50 / 60 Hz
<b>Rotation Angle</b>	350 Degree
<b>Swivel Angle</b>	90 Degree
<b>Product weight</b>	674 g
<b>Connection Type</b>	Clamp
<b>Mounting Type</b>	Top mounting
<b>Mounting Location</b>	Inside
<b>Mounting Area</b>	Ceiling installation
<b>Rated Input Voltage</b>	220-240 V/AC
<b>Power</b>	7.5 W
<b>Control</b>	Dimmable via optional light source
<b>Dimmable</b>	Yes
<b>Motion Detector</b>	No
<b>Protection Class</b>	Protection class I /protective grounding
<b>Socket Description</b>	GU10
<b>Execution</b>	Without lamp
<b>Light direction</b>	Below
<b>Turning and</b>	

<b>Swiveling Range</b>	Rotatable
<b>Height</b>	125 mm
<b>Diameter</b>	60 mm
<b>IP Protection Class</b>	IP 20

