

Battery-powered light - Set, Miram stand + head red bundle, 2.2 W, Touch DIM, 3,



Prices

| List price (VAT included) | 136.85 EUR per 1 |
|------------------------------|---------------------|
| Minimum order | 1 |
| quantity | 1 |
| Order step | |

Image similar

Information

Order number EAN

620097 4042943168269

Brand



Description

- Long battery life (10 h)
- Easy charging via USB-A to USB-C cable (included)
- High luminous flux
- Infinitely dimmable using touch sensor
- Splash water protection

Combine & shine - with the MIRAM series, the sky is the limit for your creativity. Simply combine your favourite colour of lamp head with either a base, wall bracket or pendant fixture. Create your unique lighting in an instant and redesign it any time without tools. Flexible, simple, striking - MIRAM Combine & Shine

Features

| RRP incl. VAT Housing Material Housing Color | 136.85 EUR Aluminium Red |
|--|--------------------------------|
| Housing Color, Color System | Ruby red RAL 3003 |
| Operating Mode | Constant voltage |
| Base width | 102 mm |
| Connection Type | USB type C |
| Light Source | Light source not changeable |
| Light Source | LED |
| Luminous Efficiency | 89.1 lm/W |
| Light Distribution | Asymetric |
| Colour Consistency | 6 SDCM |
| Switching Cycles | 15000 |
| Power Supply Unit incl. | No |
| Number of Accumulator/Battery | 1 |
| Type of Accumulator /Battery | Li-Ion battery type 18650 |
| Accumulator/Battery Chemical System | Li-lon |
| Accumulator/Battery Voltage | 3.7 V/DC |

Accumulator/Battery



4400 mAh Capacity

Accumulator 12 h **Operating Time**

Accumulator 5-7 h **Charging Time**

Working

-20 to 45 °C **Temperature**

Storage Temperature -40 to 60 °C

Mounting Location Inside

Scope of Delivery 1x USB C charging cable

Rated Input Voltage 3.7 V/DC

Accumulator/Battery

Yes Operated

2.2 W Rated Input

> Control Touch-Sensor

Dimmable Yes **Motion Detector** No

Protection Class Protection class III/safety

extra-low voltage

Lightcolor Warm white (WW)

Color Temperature 3000 K **Colour Rendering**

80 Index (Ra)

Rated Luminous Flux 196 lm

Rated Angle of

47 Degree

Reflection Length 120 mm Width 120 mm Height 300 mm Diameter 120 mm

IP Protection Class IP 54 Life Time L70 / B50 30000 h







IP54

