

## Battery-powered light - Set, Miram stand + head grey bundle, 2.2 W, Touch DIM, 3



Image similar

### Prices

<b>List price</b> (VAT included)	136.85 EUR per 1
<b>Minimum order quantity</b>	1
<b>Order step</b>	1

### Information

<b>Order number</b>	620099
<b>EAN</b>	4042943168283
<b>Brand</b>	 <b>DEKOLIGHT</b>

### Description

- Long battery life (10 h)
- Easy charging via USB-A to USB-C cable (included)
- High luminous flux
- Infinitely dimmable using touch sensor
- Splash water protection

Combine & shine - with the MIRAM series, the sky is the limit for your creativity. Simply combine your favourite colour of lamp head with either a base, wall bracket or pendant fixture. Create your unique lighting in an instant and redesign it any time without tools. Flexible, simple, striking - MIRAM Combine & Shine

### Features

<b>RRP incl. VAT</b>	136.85 EUR
<b>Housing Material</b>	Aluminium
<b>Housing Color</b>	Grey
<b>Operating Mode</b>	Constant voltage
<b>Base width</b>	102 mm
<b>Connection Type</b>	USB type C
<b>Light Source</b>	Light source not changeable
<b>Light Source</b>	LED
<b>Luminous Efficiency</b>	89.1 lm/W
<b>Light Distribution</b>	Asymmetric
<b>Colour Consistency</b>	6 SDCM
<b>Switching Cycles</b>	15000
<b>Power Supply Unit incl.</b>	No
<b>Number of Accumulator/Battery</b>	1
<b>Type of Accumulator /Battery</b>	Li-Ion battery type 18650
<b>Accumulator/Battery Chemical System</b>	Li-Ion
<b>Accumulator/Battery Voltage</b>	3.7 V/DC
<b>Accumulator/Battery Capacity</b>	4400 mAh
<b>Accumulator</b>	

<b>Operating Time</b>	12 h
<b>Accumulator</b>	
<b>Charging Time</b>	5-7 h
<b>Working</b>	
<b>Temperature</b>	-20 to 45 °C
<b>Storage Temperature</b>	-40 to 60 °C
<b>Mounting Location</b>	Inside
<b>Scope of Delivery</b>	1x USB C charging cable
<b>Rated Input Voltage</b>	3.7 V/DC
<b>Accumulator/Battery</b>	
<b>Operated</b>	Yes
<b>Rated Input</b>	2.2 W
<b>Control</b>	Touch-Sensor
<b>Dimmable</b>	Yes
<b>Motion Detector</b>	No
<b>Protection Class</b>	Protection class III/safety extra-low voltage
<b>Lightcolor</b>	Warm white (WW)
<b>Color Temperature</b>	3000 K
<b>Colour Rendering</b>	
<b>Index (Ra)</b>	80
<b>Rated Luminous Flux</b>	196 lm
<b>Rated Angle of</b>	
<b>Reflection</b>	47 Degree
<b>Length</b>	120 mm
<b>Width</b>	120 mm
<b>Height</b>	300 mm
<b>Diameter</b>	120 mm
<b>IP Protection Class</b>	IP 54
<b>Life Time L70 / B50</b>	30000 h

