

# Battery-powered light - Set, Miram stand + head blue bundle, 2.2 W, Touch DIM, 3



### **Prices**

List price	136.85 EUR
(VAT included)	per 1
Minimum order	1
quantity	1
Order step	

Image similar

## Information

Order number EAN

4042943168306

620101

Brand (

**DEKO**LIGHT

# **Description**

- Long battery life (10 h)
- Easy charging via USB-A to USB-C cable (included)
- High luminous flux
- Infinitely dimmable using touch sensor
- Splash water protection

Combine & shine - with the MIRAM series, the sky is the limit for your creativity. Simply combine your favourite colour of lamp head with either a base, wall bracket or pendant fixture. Create your unique lighting in an instant and redesign it any time without tools. Flexible, simple, striking - MIRAM Combine & Shine

#### **Features**

reatures	
RRP incl. VAT	136.85 EUR
<b>Housing Material</b>	Aluminium
<b>Housing Color</b>	Blue
<b>Operating Mode</b>	Constant voltage
Base width	102 mm
Connection Type	USB type C
Light Source	Light source not changeable
Light Source	LED
Luminous Efficiency	89.1 lm/W
<b>Light Distribution</b>	Asymetric
Colour Consistency	6 SDCM
Switching Cycles	15000
Power Supply Unit incl.	No
Number of Accumulator/Battery	1
Type of Accumulator /Battery	Li-lon battery type 18650
Accumulator/Battery Chemical System	Li-lon
Accumulator/Battery Voltage	3.7 V/DC
Accumulator/Battery Capacity	4400 mAh

Accumulator



**Operating Time** 12 h Accumulator 5-7 h **Charging Time** 

Working -20 to 45 °C Temperature -40 to 60 °C **Storage Temperature** 

**Mounting Location** Inside

Scope of Delivery 1x USB C charging cable

**Rated Input Voltage** 3.7 V/DC

Accumulator/Battery

Yes Operated

**Rated Input** 2.2 W

Control Touch-Sensor

Dimmable Yes **Motion Detector** No

Protection class III/safety **Protection Class** 

extra-low voltage

Lightcolor Warm white (WW)

**Color Temperature** 3000 K **Colour Rendering** 

80

Index (Ra)

**Rated Luminous Flux** 196 lm

Rated Angle of

47 Degree Reflection

Length 120 mm Width 120 mm Height 300 mm Diameter 120 mm

**IP Protection Class** IP 54 Life Time L70 / B50 30000 h









